

# NEMA

<b>MOTOR MODEL:</b>	BK3-CI-TF-326T-6-BR-G-30
<b>FACTORY TYPE:</b>	-

## NEMA Cast Iron, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	30.0	-
Speed, RPM	1136	-
Voltage	230/460/796	-
# Phase	-	
Full Load Amps	71/35.5/20.5	-
Power Factor	0.86	3.0
Nominal Efficiency	91.1	-
3/4 Load Efficiency	-	-
Service Factor	1.15	-
KVA Code	F	-
FL Amps. @ 208 V	-	-
LRC @ 60Hz HV	273.0	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	12	
Connection	-	
Coil Resistance	-	
Date Code	-	
Load	Efficiency %	P.F.
50%	91.67	0.7599
75%	91.92	0.9341
100%	91.1	0.8596
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	-	
3D Image Link		
Not available for this motor		

GENERAL DATA		
Frame Size	326T	
Frame Enclosure	TEFC	
Mounting	Rigid	
Insulation Class	F	
Duty	-	
NEMA Design	D	
Frame Material	Cast Iron	
Ingress Protection	55	
Tropicalization	-	
Cable Entry	-	
Feet Removable	-	
Double Drilled	-	
Paint Color	-	
Paint RAL	-	
Weight lb	562.0	
MECHANICAL DATA		
DE Bearing	6312C3	
NDE Bearing	6312C3	
dB No-Load	-	
Rotor Wk <sup>2</sup> , Lb-Ft <sup>2</sup>	-	
Comp Ring (wavy washer)	-	
TORQUE VALUES		
	Torque lb-ft	% FLT
Locked Rotor Torque	279.53	210.0
Pull-Up Torque	173.04	130.0
Breakdown Torque	315.47	237.0
Full Load Torque	133.11	100.0
SITE CONDITIONS		
Ambient Temp °C	-	
Altitude Above Sea Level m	-	

\*This report valid for above Date Code and newer models, please contact Techttop for more info.




# Pump Motors

## NEMA

<b>MOTOR MODEL:</b>	BK3-CI-TF-326T-6-BR-G-30
<b>FACTORY TYPE:</b>	-

### NEMA Cast Iron, TEFC

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	279.53	210.0	Start Configuration
Pull-Up Torque	173.04	130.0	Starting Current (A)
Breakdown Torque	315.47	237.0	No-Load Current (A)
Full Load	133.11	100.0	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	0.0	11.42	0.6519	1199.0	0.0	-
25	7.5	13.79	6.25	1192.7	88.0	0.5688
50	15.0	19.82	12.0	1184.6	91.67	0.7599
75	22.5	27.01	17.95	1174.9	91.92	0.9341
100	30.0	35.26	24.15	1163.7	91.1	0.8596
125	37.5	44.48	30.66	1150.8	89.69	0.8651

Techtop Industries  
 2815 Colonnades Court  
 Peachtree Corners, GA 30071  
 Tel: 678-436-5540  
 E-Mail: info@techttopind.com