



EPAct

**NEMA**

<b>MOTOR MODEL:</b>	BL3-AL-TF-56C-2-B-D-1
<b>FACTORY TYPE:</b>	TFA

EPAct NEMA Cast Aluminum, TEFC

<b>ELECTRICAL DATA</b>		
	60 Hz	50 Hz
Horsepower	1.0	1.0
Speed, RPM	3470	-
Voltage	208-230/460	-
# Phase	3	
Full Load Amps	3.1-3.18/1.59	-
Power Factor	0.77	-
Nominal Efficiency	76.8	-
3/4 Load Efficiency	-	-
Service Factor	1.15	-
KVA Code	K	-
FL Amps. @ 208 V	3.1	-
Locked Rotor Current	-	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	9	
Connection	YY/Y	
Coil Resistance	-	
Load	Efficiency %	P.F.
50%	-	-
75%	-	-
100%	-	-
<b>FULL LOAD TEMPERATURE RISE</b>		
FL Temp Rise °C	-	-
<b>3D Image Link</b>		
Not available for this motor		

<b>GENERAL DATA</b>		
Frame Size	56C	
Frame Enclosure	TEFC	
Mounting	Rigid/C-Flange	
Insulation Class	F	
Duty	Cont. / S1	
NEMA Design	B	
Frame Material	Cast Aluminum	
Ingress Protection	55	
Tropicalization	true	
Cable Entry	1-NPT 1/2"	
Feet Removable	true	
Double Drilled	-	
Paint Color	Graphite Gray	
Paint RAL	7024	
Weight lb	20.3	
<b>MECHANICAL DATA</b>		
DE Bearing	6204ZZ	
NDE Bearing	6204ZZ	
dB No-Load	-	
Rotor Wk <sup>2</sup> , Lb-Ft <sup>2</sup>	-	
Comp Ring (wavey washer)	NDE	
TORQUE VALUES	Torque lb-ft	% FLT
Locked Rotor Torque	-	-
Pull-Up Torque	-	-
Breakdown Torque	-	-
Full Load Torque	-	-
<b>SITE CONDITIONS</b>		
Ambient Temp °C	40	
Altitude Above Sea Level m	1000	



EPAct

**NEMA**

<b>MOTOR MODEL:</b>	BL3-AL-TF-56C-2-B-D-1
<b>FACTORY TYPE:</b>	TFA

EPAct NEMA Cast Aluminum, TEFC

Non Sinusoidal (VFD) Output 1.0HP, 3470 RPM

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	-	-	Start Configuration
Pull-Up Torque	-	-	Starting Current (A)
Breakdown Torque	-	-	No-Load Current (A)
Full Load	-	-	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	-	-	-	-	-
25	-	-	-	-	-	-
50	-	-	-	-	-	-
75	-	-	-	-	-	-
100	-	-	-	-	-	-
125	-	-	-	-	-	-