



IE1

IEC

<b>MOTOR MODEL:</b>	BL3-AL-TF-63B34-2-B-D-.25
<b>FACTORY TYPE:</b>	TM

IE1 IEC Cast Aluminum, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	0.25	0.25
Speed, RPM	3330	2680
Voltage	230/460	190/380
# Phase	3	
Full Load Amps	0.88/0.44	1.06/0.53
Power Factor	0.74	-
Nominal Efficiency	69.5	-
3/4 Load Efficiency	-	-
Service Factor	1.15	1.0
KVA Code	H	E
FL Amps. @ 208 V	0.9	-
Locked Rotor Current	-	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	9	
Connection	YY/Y	
Coil Resistance	-	
<b>Load</b>	<b>Efficiency %</b>	<b>P.F.</b>
50%	-	-
75%	-	-
100%	-	-
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	-	-
3D Image Link		
Not available for this motor		

GENERAL DATA	
Frame Size	63B34
Frame Enclosure	TEFC
Mounting	B34
Insulation Class	F
Duty	Cont. / S1
NEMA Design	-
Frame Material	Cast Aluminum
Ingress Protection	55
Tropicalization	true
Cable Entry	1-M16X1.5
Feet Removable	true
Double Drilled	-
Paint Color	Graphite Gray
Paint RAL	7024
Weight lb	8.8
MECHANICAL DATA	
DE Bearing	6201ZZ
NDE Bearing	6201ZZ
dB No-Load	-
Rotor Wk <sup>2</sup> , Lb-Ft <sup>2</sup>	-
Comp Ring (wavey washer)	-
TORQUE VALUES	
Locked Rotor Torque	-
Pull-Up Torque	-
Breakdown Torque	-
Full Load Torque	-
SITE CONDITIONS	
Ambient Temp °C	40
Altitude Above Sea Level m	1000



IE1

IEC

<b>MOTOR MODEL:</b>	BL3-AL-TF-63B34-2-B-D-.25
<b>FACTORY TYPE:</b>	TM

IE1 IEC Cast Aluminum, TEFC

Non Sinusoidal (VFD) Output 0.25HP, 3330 RPM

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	-	-	Start Configuration
Pull-Up Torque	-	-	Starting Current (A)
Breakdown Torque	-	-	No-Load Current (A)
Full Load	-	-	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	-	-	-	-	-
25	-	-	-	-	-	-
50	-	-	-	-	-	-
75	-	-	-	-	-	-
100	-	-	-	-	-	-
125	-	-	-	-	-	-