

| | |
|----------------------|-------------------------|
| MOTOR MODEL: | GA3-AL-TF-145JM-2-B-D-3 |
| FACTORY TYPE: | TFA |

EPAct NEMA Cast Aluminum, TEFC

| ELECTRICAL DATA | | |
|------------------------------|--------------|-------|
| | 60 Hz | 50 Hz |
| Horsepower | 3.0 | 3.0 |
| Speed, RPM | 3490 | - |
| Voltage | 230/460 | - |
| # Phase | 3 | |
| Full Load Amps | 7.78/3.89 | - |
| Power Factor | 0.83 | - |
| Nominal Efficiency | 85.5 | - |
| 3/4 Load Efficiency | - | - |
| Service Factor | 1.25 | - |
| KVA Code | L | - |
| FL Amps. @ 208 V | 7.98 | - |
| Locked Rotor Current | - | - |
| Start Capacitor | - | |
| Start Capacitor V | - | |
| Run Capacitor | - | |
| Run Capacitor V | - | |
| Number of Leads | 9 | |
| Connection | YY/Y | |
| Coil Resistance | - | |
| | | |
| | | |
| Load | Efficiency % | P.F. |
| 50% | - | - |
| 75% | - | - |
| 100% | - | - |
| | | |
| FULL LOAD TEMPERATURE RISE | | |
| FL Temp Rise °C | 38.0 | 55.0 |
| | | |
| 3D Image Link | | |
| Not available for this motor | | |

| GENERAL DATA | | |
|--|----------------|-------|
| Frame Size | 145JM | |
| Frame Enclosure | TEFC | |
| Mounting | Rigid/C-Flange | |
| Insulation Class | F | |
| Duty | Cont. / S1 | |
| NEMA Design | A | |
| Frame Material | Cast Aluminum | |
| Ingress Protection | 55 | |
| Tropicalization | true | |
| Cable Entry | 1-NPT 3/4" | |
| Feet Removable | true | |
| Double Drilled | - | |
| Paint Color | Graphite Gray | |
| Paint RAL | 7024 | |
| Weight lb | 50.0 | |
| | | |
| MECHANICAL DATA | | |
| DE Bearing | 6206ZZ | |
| NDE Bearing | 6205ZZ | |
| dB No-Load | - | |
| Rotor Wk ² , Lb-Ft ² | - | |
| Comp Ring (wavy washer) | NDE | |
| | | |
| TORQUE VALUES | Torque lb-ft | % FLT |
| Locked Rotor Torque | - | - |
| Pull-Up Torque | - | - |
| Breakdown Torque | - | - |
| Full Load Torque | - | - |
| | | |
| SITE CONDITIONS | | |
| Ambient Temp °C | 40 | |
| Altitude Above Sea Level m | 1000 | |



Pump Motors


NEMA

| | |
|----------------------|-------------------------|
| MOTOR MODEL: | GA3-AL-TF-145JM-2-B-D-3 |
| FACTORY TYPE: | TFA |

EPAct NEMA Cast Aluminum, TEFC

Non Sinusoidal (VFD) Output 3.0HP, 3490 RPM

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

| Torque Values | Torque lb-ft | % FLT | Performance Values |
|---------------------|--------------|-------|----------------------|
| Locked Rotor Torque | - | - | Start Configuration |
| Pull-Up Torque | - | - | Starting Current (A) |
| Breakdown Torque | - | - | No-Load Current (A) |
| Full Load | - | - | No-Load Power Factor |

| % Load | Horsepower | Current, Amps | Input power, Kilowatts | Speed, RPM | Efficiency | PF |
|--------|------------|---------------|------------------------|------------|------------|----|
| 0 | - | - | - | - | - | - |
| 25 | - | - | - | - | - | - |
| 50 | - | - | - | - | - | - |
| 75 | - | - | - | - | - | - |
| 100 | - | - | - | - | - | - |
| 125 | - | - | - | - | - | - |

Techtop Industries
 2815 Colonnades Court
 Peachtree Corners, GA 30071
 Tel: 678-436-5540
 E-Mail: info@techttopind.com