






Pump Motors

**NEMA**

|                      |                         |
|----------------------|-------------------------|
| <b>MOTOR MODEL:</b>  | GA3-AL-TF-56J-2-B-D-1.5 |
| <b>FACTORY TYPE:</b> | TFA                     |

EPAct NEMA Cast Aluminum, TEFC

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

| Torque Values       | Torque lb-ft | % FLT | Performance Values   |
|---------------------|--------------|-------|----------------------|
| Locked Rotor Torque | -            | -     | Start Configuration  |
| Pull-Up Torque      | -            | -     | Starting Current (A) |
| Breakdown Torque    | -            | -     | No-Load Current (A)  |
| Full Load           | -            | -     | No-Load Power Factor |

| % Load | Horsepower | Current, Amps | Input power, Kilowatts | Speed, RPM | Efficiency | PF |
|--------|------------|---------------|------------------------|------------|------------|----|
| 0      | -          | -             | -                      | -          | -          | -  |
| 25     | -          | -             | -                      | -          | -          | -  |
| 50     | -          | -             | -                      | -          | -          | -  |
| 75     | -          | -             | -                      | -          | -          | -  |
| 100    | -          | -             | -                      | -          | -          | -  |
| 125    | -          | -             | -                      | -          | -          | -  |