



# Pump Motors

## NEMA

<b>MOTOR MODEL:</b>	GA3-CI-TF-286JP-2-BR-D-30
<b>FACTORY TYPE:</b>	TFC

### EPAct NEMA Cast Iron, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	30.0	30.0
Speed, RPM	3550	-
Voltage	230/460	-
# Phase	3	
Full Load Amps	69.0/34.5	-
Power Factor	0.9	-
Nominal Efficiency	91.0	-
3/4 Load Efficiency	-	-
Service Factor	1.25	-
KVA Code	F	-
FL Amps. @ 208 V	-	-
Locked Rotor Current	-	-
Start Capacitor	-	-
Start Capacitor V	-	-
Run Capacitor	-	-
Run Capacitor V	-	-
Number of Leads	12	
Connection	DD/D	
Coil Resistance	0.2	
Date Code	-	
<b>Load</b>	<b>Efficiency %</b>	<b>P.F.</b>
50%	-	-
75%	-	-
100%	-	-
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	60.0	72.0
3D Image Link		
Not available for this motor		

GENERAL DATA	
Frame Size	286JP
Frame Enclosure	TEFC
Mounting	Rigid/C-Flange
Insulation Class	F
Duty	Cont. / S1
NEMA Design	B
Frame Material	Cast Iron
Ingress Protection	55
Tropicalization	true
Cable Entry	1-NPT 1-1/2"
Feet Removable	true
Double Drilled	true
Paint Color	Graphite Gray
Paint RAL	7024
Weight lb	419.0
MECHANICAL DATA	
DE Bearing	6311 C3
NDE Bearing	6311 C3
dB No-Load	-
Rotor Wk <sup>2</sup> , Lb-Ft <sup>2</sup>	1.93402
Comp Ring (wavey washer)	NDE
TORQUE VALUES	
	<b>Torque lb-ft</b> <b>% FLT</b>
Locked Rotor Torque	-      -
Pull-Up Torque	-      -
Breakdown Torque	-      -
Full Load Torque	-      -
SITE CONDITIONS	
Ambient Temp °C	40
Altitude Above Sea Level m	1000

\*This report valid for above Date Code and newer models, please contact Techtop for more info.



# Pump Motors

## NEMA

<b>MOTOR MODEL:</b>	GA3-CI-TF-286JP-2-BR-D-30
<b>FACTORY TYPE:</b>	TFC

### EPAct NEMA Cast Iron, TEFC

Non Sinusoidal (VFD) Output 30.0HP, 3550 RPM

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	-	-	Start Configuration
Pull-Up Torque	-	-	Starting Current (A)
Breakdown Torque	-	-	No-Load Current (A)
Full Load	-	-	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	-	-	-	-	-
25	-	-	-	-	-	-
50	-	-	-	-	-	-
75	-	-	-	-	-	-
100	-	-	-	-	-	-
125	-	-	-	-	-	-