



Pump Motors

NEMA

| | |
|----------------------|---------------------------|
| MOTOR MODEL: | GA3-CI-TF-286JP-4-BR-D-30 |
| FACTORY TYPE: | TFC |

EPAct NEMA Cast Iron, TEFC

| ELECTRICAL DATA | | |
|------------------------------|--------------|-------|
| | 60 Hz | 50 Hz |
| Horsepower | 30.0 | 30.0 |
| Speed, RPM | 1770 | - |
| Voltage | 230/460 | - |
| # Phase | 3 | |
| Full Load Amps | 71.0/35.5 | - |
| Power Factor | 0.86 | - |
| Nominal Efficiency | 92.4 | - |
| 3/4 Load Efficiency | - | - |
| Service Factor | 1.25 | - |
| KVA Code | F | - |
| FL Amps. @ 208 V | - | - |
| LRC @ 60Hz HV | - | - |
| Start Capacitor | - | |
| Start Capacitor V | - | |
| Run Capacitor | - | |
| Run Capacitor V | - | |
| Number of Leads | 12 | |
| Connection | DD/D | |
| Coil Resistance | 0.25 | |
| Date Code | - | |
| | | |
| Load | Efficiency % | P.F. |
| 50% | - | - |
| 75% | - | - |
| 100% | - | - |
| | | |
| FULL LOAD TEMPERATURE RISE | | |
| FL Temp Rise °C | 60.0 | 85.0 |
| | | |
| 3D Image Link | | |
| Not available for this motor | | |

| GENERAL DATA | | |
|--|----------------|-------|
| Frame Size | 286JP | |
| Frame Enclosure | TEFC | |
| Mounting | Rigid/C-Flange | |
| Insulation Class | F | |
| Duty | Cont. / S1 | |
| NEMA Design | B | |
| Frame Material | Cast Iron | |
| Ingress Protection | 55 | |
| Tropicalization | true | |
| Cable Entry | 1-NPT 1-1/2" | |
| Feet Removable | true | |
| Double Drilled | true | |
| Paint Color | Graphite Gray | |
| Paint RAL | 7024 | |
| Weight lb | 404.0 | |
| | | |
| MECHANICAL DATA | | |
| DE Bearing | 6311 C3 | |
| NDE Bearing | 6311 C3 | |
| dB No-Load | - | |
| Rotor Wk ² , Lb-Ft ² | 3.8111 | |
| Comp Ring (wavy washer) | NDE | |
| | | |
| TORQUE VALUES | Torque lb-ft | % FLT |
| Locked Rotor Torque | - | - |
| Pull-Up Torque | - | - |
| Breakdown Torque | - | - |
| Full Load Torque | - | - |
| | | |
| SITE CONDITIONS | | |
| Ambient Temp °C | 40 | |
| Altitude Above Sea Level m | 1000 | |

*This report valid for above Date Code and newer models, please contact Techtop for more info.




Pump Motors

NEMA

| | |
|----------------------|---------------------------|
| MOTOR MODEL: | GA3-CI-TF-286JP-4-BR-D-30 |
| FACTORY TYPE: | TFC |

EPAct NEMA Cast Iron, TEFC

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

| Torque Values | Torque lb-ft | % FLT | Performance Values |
|---------------------|--------------|-------|----------------------|
| Locked Rotor Torque | - | - | Start Configuration |
| Pull-Up Torque | - | - | Starting Current (A) |
| Breakdown Torque | - | - | No-Load Current (A) |
| Full Load | - | - | No-Load Power Factor |

| % Load | Horsepower | Current, Amps | Input power, Kilowatts | Speed, RPM | Efficiency | PF |
|--------|------------|---------------|------------------------|------------|------------|----|
| 0 | - | - | - | - | - | - |
| 25 | - | - | - | - | - | - |
| 50 | - | - | - | - | - | - |
| 75 | - | - | - | - | - | - |
| 100 | - | - | - | - | - | - |
| 125 | - | - | - | - | - | - |