

Techtop Industries Nameplate and Performance Data

NAMEPLATE DATA		
	60 Hz.	50 Hz.
Horsepower	2.0	2.0
Frame Size	184TC	
Speed, RPM	1175	970
Voltage	3 Phase US	190/380
# Phase	3	
Full Load Amps	6.26/3.13	7.18/3.59
Power Factor	0.68	-
Nominal Efficiency	88.5	88.1
3/4 Load Efficiency	-	-
Service Factor	1.25	1.0
Duty	Cont. / S1	
FL Temp Rise °C	16.2	16.0
Enclosure	TEFC	
Ambient Temp °C	40	
KVA Code	L	J
FL Amps. @ 208 V	6.36	-
Insulation Class	F	
NEMA Design	B	
Weight	62.0	
DE Bearing	6306ZZ	
NDE Bearing	6206ZZ	
dB No-Load	-	
Rotor Wk ² , Lb-Ft ²	-	
Start Capacitor		
Start Capacitor V	-	
Run Capacitor		
Run Capacitor V	-	
Number of Leads	9	
Connection	YY/Y	
Coil Resistance	5.9	

Motor Model:	GR3-AL-TF-184TC-6-B-D-2
---------------------	--------------------------------

Performance Load Values:

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	2.33	-	-	-	-
25	0.5	2.4	489.99	1194.8	76.53	0.26
50	1.0	2.59	878.05	1190.2	85.42	0.43
75	1.5	2.89	1275.6	1185.2	88.19	0.55
100	2.0	3.28	1683.8	1179.8	89.08	0.64
125	2.5	3.74	2103.5	1174.1	89.14	0.71
150	3.0	4.26	2535.8	1168.1	88.73	0.75
SF	-	-	-	-	-	-

	Torque, Lb-Ft	% Full Load Torque	Speed, RPM	Current Amps.
Locked Rotor Torque	31.1984	3.47	-	8.48
Pull Up Torque	23.8258	2.65	-	-
Breakdown Torque	39.3801	4.38	-	-
Full Load	8.99088	100.0	-	3.28

Speed Torque Curve

Please contact Techttop for image.

Dimensional Drawing

DRAWING UNAVAILABLE CONTACT TECHTOP

Dimensions are for reference only. Allowance should be made for minor deviations in non standard specified properties.

3D Image Link: Not available for this motor

Techttop Industries
 2815 Colonnades Court
 Peachtree Corners, GA 30071
 Tel: 678-436-5540
 E-Mail: info@techttopind.com