

NEMA

MOTOR MODEL:	GR3-AL-TF-213T-2-B-D-7.5
FACTORY TYPE:	TXA

Premium NEMA Cast Aluminum, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	7.5	7.5
Speed, RPM	3520	2910
Voltage	230/460	190/380
# Phase	3	
Full Load Amps	17.0/8.48	19.9/9.95
Power Factor	0.91	-
Nominal Efficiency	89.5	88.5
3/4 Load Efficiency	-	-
Service Factor	1.25	1.0
KVA Code	K	H
FL Amps. @ 208 V	18.7	-
Locked Rotor Current	188.462	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	9	
Connection	YY/Y	
Coil Resistance	-	
Load	Efficiency %	P.F.
50%	88.01	0.79
75%	90.04	0.86
100%	90.54	0.89
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	34.9	43.3
3D Image Link		
GR3-AL-TF-213T-2-B-D-7.5		

GENERAL DATA			
Frame Size	213T		
Frame Enclosure	TEFC		
Mounting	Rigid		
Insulation Class	F		
Duty	Cont. / S1		
NEMA Design	A		
Frame Material	Cast Aluminum		
Ingress Protection	55		
Tropicalization	true		
Cable Entry	1-NPT 1"		
Feet Removable	true		
Double Drilled	-		
Paint Color	Graphite Gray		
Paint RAL	7024		
Weight lb	95.0		
MECHANICAL DATA			
DE Bearing	6308ZZ		
NDE Bearing	6208ZZ		
dB No-Load	-		
Rotor Wk ² , Lb-Ft ²	-		
Comp Ring (wavey washer)	NDE		
TORQUE VALUES		Torque lb-ft	% FLT
Locked Rotor Torque	38.6162	354.0	
Pull-Up Torque	11.5631	106.0	
Breakdown Torque	45.925	421.0	
Full Load Torque	10.9085	100.0	
SITE CONDITIONS			
Ambient Temp °C	40		
Altitude Above Sea Level m	1000		



NEMA Premium


MOTOR MODEL:	GR3-AL-TF-213T-2-B-D-7.5
FACTORY TYPE:	TXA

NEMA

Premium NEMA Cast Aluminum, TEFC

Non Sinusoidal (VFD) Output 7.5HP, 3520 RPM

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	38.6162	354.0	Start Configuration
Pull-Up Torque	11.5631	106.0	Starting Current (A)
Breakdown Torque	45.925	421.0	No-Load Current (A)
Full Load	10.9085	100.0	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	5.78	-	-	-	-
25	1.875	7.16	1700.8	3584.8	80.84	0.6
50	3.75	9.98	3124.7	3571.1	88.01	0.79
75	5.625	13.32	4581.2	3556.7	90.04	0.86
100	7.5	17.04	6074.7	3541.5	90.54	0.89
125	9.375	21.03	7608.1	3525.5	90.36	0.91

Techtop Industries
 2815 Colonnades Court
 Peachtree Corners, GA 30071
 Tel: 678-436-5540
 E-Mail: info@techttopind.com