

## Techtop Industries Nameplate and Performance Data

| NAMEPLATE DATA                             |            |           |
|--|------------|-----------|
|  | 60 Hz      | 50 Hz     |
| Horsepower                                 | 10.0       | 10.0      |
| Frame Size                                 | 215JP      |           |
| Speed, RPM                                 | 3520       | 2910      |
| Voltage                                    | 230/460    | 190/380   |
| # Phase                                    | 3          |           |
| Full Load Amps                             | 22.6/11.3  | 26.6/13.3 |
| Power Factor                               | 0.92       | -         |
| Nominal Efficiency                         | 90.2       | 89.5      |
| 3/4 Load Efficiency                        | -          | -         |
| Service Factor                             | 1.25       | 1.0       |
| Duty                                       | Cont. / S1 |           |
| FL Temp Rise °C                            | 42.6       | 45.3      |
| Enclosure                                  | TEFC       |           |
| Ambient Temp °C                            | 40         |           |
| KVA Code                                   | L          | H         |
| FL Amps. @ 208 V                           | 25.8       | -         |
| Insulation Class                           | F          |           |
| NEMA Design                                | A          |           |
| Weight                                     | 115.0      |           |
| DE Bearing                                 | 6308ZZ     |           |
| NDE Bearing                                | 6208ZZ     |           |
| dB No-Load                                 | -          |           |
| Rotor Wk <sup>2</sup> , Lb-Ft <sup>2</sup> | -          |           |
| Start Capacitor                            | -          |           |
| Start Capacitor V                          | -          |           |
| Run Capacitor                              | -          |           |
| Run Capacitor V                            | -          |           |
| Number of Leads                            | 9          |           |
| Connection                                 | YY/Y       |           |
| Coil Resistance                            | -          |           |

|                     |                                 |
|---------------------|---------------------------------|
| <b>Motor Model:</b> | <b>GR3-AL-TF-215JP-2-B-D-10</b> |
|---------------------|---------------------------------|

Performance Load Values:

| % Load | Horsepower | Current, Amps | Input power, Kilowatts | Speed, RPM | Efficiency | PF |
|--------|------------|---------------|------------------------|------------|------------|----|
| 0      | -          | -             | -                      | -          | -          | -  |
| 25     | 2.5        | -             | -                      | -          | -          | -  |
| 50     | 5.0        | -             | -                      | -          | -          | -  |
| 75     | 7.5        | -             | -                      | -          | -          | -  |
| 100    | 10.0       | -             | -                      | -          | -          | -  |
| 125    | 12.5       | -             | -                      | -          | -          | -  |
| 150    | 15.0       | -             | -                      | -          | -          | -  |
| SF     | -          | -             | -                      | -          | -          | -  |

|                     | Torque, Lb-Ft | % Full Load Torque | Speed, RPM | Current Amps. |
|---------------------|---------------|--------------------|------------|---------------|
| Locked Rotor Torque | 42.4348       | 2.83               | -          | 239.516       |
| Pull Up Torque      | 6.44769       | 0.43               | -          | -             |
| Breakdown Torque    | 67.9257       | 4.53               | -          | -             |
| Full Load           | 14.9946       | 100.0              | -          | 22.66         |

### Speed Torque Curve

Please contact Techtop for image.

### Dimensional Drawing

Please contact Techtop for image.

Dimensions are for reference only. Allowance should be made for minor deviations in non standard specified properties.

3D Image Link: Not available for this motor