

**NEMA**

<b>MOTOR MODEL:</b>	GR3-AL-TF-56C-4-B-F-.33
<b>FACTORY TYPE:</b>	TXA

## Premium NEMA Cast Aluminum, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	0.33	0.33
Speed, RPM	1750	-
Voltage	575	-
# Phase	3	
Full Load Amps	0.53	-
Power Factor	0.63	-
Nominal Efficiency	74.0	-
3/4 Load Efficiency	-	-
Service Factor	1.25	-
KVA Code	K	-
FL Amps. @ 208 V	-	-
Locked Rotor Current	-	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	3	
Connection	Y	
Coil Resistance	-	
Load	Efficiency %	P.F.
50%	-	-
75%	-	-
100%	-	-
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	21.7	-
3D Image Link		
<a href="#">GR3-AL-TF-56C-4-B-F-.33</a>		

GENERAL DATA			
Frame Size	56C		
Frame Enclosure	TEFC		
Mounting	Rigid/C-Flange		
Insulation Class	F		
Duty	Cont. / S1		
NEMA Design	B		
Frame Material	Cast Aluminum		
Ingress Protection	55		
Tropicalization	true		
Cable Entry	1-NPT 1/2"		
Feet Removable	true		
Double Drilled	-		
Paint Color	Graphite Gray		
Paint RAL	7024		
Weight lb	15.8		
MECHANICAL DATA			
DE Bearing	6204ZZ		
NDE Bearing	6204ZZ		
dB No-Load	-		
Rotor Wk <sup>2</sup> , Lb-Ft <sup>2</sup>	-		
Comp Ring (wavy washer)	NDE		
TORQUE VALUES		Torque lb-ft	% FLT
Locked Rotor Torque	-	-	
Pull-Up Torque	-	-	
Breakdown Torque	-	-	
Full Load Torque	-	-	
SITE CONDITIONS			
Ambient Temp °C	40		
Altitude Above Sea Level m	1000		



NEMA Premium

**NEMA**

<b>MOTOR MODEL:</b>	GR3-AL-TF-56C-4-B-F-.33
<b>FACTORY TYPE:</b>	TXA

Premium NEMA Cast Aluminum, TEFC

Non Sinusoidal (VFD) Output 0.33HP, 1750 RPM

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	-	-	Start Configuration
Pull-Up Torque	-	-	Starting Current (A)
Breakdown Torque	-	-	No-Load Current (A)
Full Load	-	-	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	-	-	-	-	-
25	-	-	-	-	-	-
50	-	-	-	-	-	-
75	-	-	-	-	-	-
100	-	-	-	-	-	-
125	-	-	-	-	-	-