




Pump Motors

NEMA

| | |
|----------------------|-------------------------|
| MOTOR MODEL: | GR3-AL-TF-56J-2-B-D-1.5 |
| FACTORY TYPE: | TXA |

Premium NEMA Cast Aluminum, TEFC

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

| Torque Values | Torque lb-ft | % FLT | Performance Values |
|---------------------|--------------|-------|----------------------|
| Locked Rotor Torque | 7.10862 | 316.0 | Start Configuration |
| Pull-Up Torque | 6.05133 | 269.0 | Starting Current (A) |
| Breakdown Torque | 8.36838 | 372.0 | No-Load Current (A) |
| Full Load | 2.24956 | 100.0 | No-Load Power Factor |

| % Load | Horsepower | Current, Amps | Input power, Kilowatts | Speed, RPM | Efficiency | PF |
|--------|------------|---------------|------------------------|------------|------------|----|
| 0 | - | 0.99 | - | - | - | - |
| 25 | 0.375 | - | - | - | - | - |
| 50 | 0.75 | - | - | - | - | - |
| 75 | 1.125 | - | - | - | - | - |
| 100 | 1.5 | - | - | - | - | - |
| 125 | 1.875 | - | - | - | - | - |

Techtop Industries
 2815 Colonnades Court
 Peachtree Corners, GA 30071
 Tel: 678-436-5540
 E-Mail: info@techttopind.com