



IE3

IEC

MOTOR MODEL:	GR3-CI-TF-160LB3-4-BR-D-20
FACTORY TYPE:	TCX

IE3 IEC Cast Iron, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	20.0	20.0
Speed, RPM	1760	1450
Voltage	230/460	190/380
# Phase	3	
Full Load Amps	47.0/23.5	58.0/29.0
Power Factor	0.83	-
Nominal Efficiency	93.0	-
3/4 Load Efficiency	-	-
Service Factor	1.15	1.0
KVA Code	J	F
FL Amps. @ 208 V	51.97	-
LRC @ 60Hz HV	211.318	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	12	
Connection	DD/D	
Coil Resistance	-	
Date Code	-	
Load	Efficiency %	P.F.
50%	91.95	0.74
75%	92.77	0.83
100%	92.58	0.87
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	63.0	90.0
3D Image Link		
GR3-CI-TF-160LB3-4-BR-D-20		

GENERAL DATA				
Frame Size	160L			
Frame Enclosure	TEFC			
Mounting	B3			
Insulation Class	F			
Duty	Cont. / S1			
NEMA Design	A			
Frame Material	Cast Iron			
Ingress Protection	55			
Tropicalization	true			
Cable Entry	2-M32X1.5			
Feet Removable	true			
Double Drilled	-			
Paint Color	Graphite Gray			
Paint RAL	7024			
Weight lb	315.0			
MECHANICAL DATA				
DE Bearing	6309C3			
NDE Bearing	6309C3			
dB No-Load	-			
Rotor Wk ² , Lb-Ft ²	-			
Comp Ring (wavy washer)	DE			
TORQUE VALUES			Torque lb-ft	% FLT
Locked Rotor Torque	166.907	280.0		
Pull-Up Torque	122.796	206.0		
Breakdown Torque	209.826	352.0		
Full Load Torque	59.6098	100.0		
SITE CONDITIONS				
Ambient Temp °C	40			
Altitude Above Sea Level m	1000			

*This report valid for above Date Code and newer models, please contact Techtop for more info.

Techtop Industries
2815 Colonnades Court
Peachtree Corners, GA 30071
Tel: 678-436-5540
E-Mail: info@techttopind.com




IE3

IEC

MOTOR MODEL:	GR3-CI-TF-160LB3-4-BR-D-20
FACTORY TYPE:	TCX

IE3 IEC Cast Iron, TEFC

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	166.907	280.0	Start Configuration
Pull-Up Torque	122.796	206.0	Starting Current (A)
Breakdown Torque	209.826	352.0	No-Load Current (A)
Full Load	59.6098	100.0	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	8.72	-	-	-	-
25	5.0	10.25	4.28	1793.3	87.68	0.52
50	10.0	13.84	8.16	1786.6	91.95	0.74
75	15.0	18.28	12.13	1779.4	92.77	0.83
100	20.0	23.35	16.2	1771.7	92.58	0.87
125	25.0	28.86	20.39	1763.5	91.95	0.89

Techtop Industries
 2815 Colonnades Court
 Peachtree Corners, GA 30071
 Tel: 678-436-5540
 E-Mail: info@techttopind.com