



NEMA Premium

NEMA

MOTOR MODEL:	GR3-CI-TF-324T-6-BR-F-25
FACTORY TYPE:	TXC

Premium NEMA Cast Iron, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	25.0	25.0
Speed, RPM	1180	-
Voltage	575	-
# Phase	3	
Full Load Amps	24.55577035	-
Power Factor	0.81	-
Nominal Efficiency	93.0	-
3/4 Load Efficiency	-	-
Service Factor	1.25	1.0
KVA Code	M	-
FL Amps. @ 208 V	-	-
Locked Rotor Current	-	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	6	
Connection	D	
Coil Resistance	-	
Date Code	-	
Load	Efficiency %	P.F.
50%	91.71	0.64
75%	92.78	0.76
100%	92.81	0.82
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	52.0	-
3D Image Link		
GR3-CI-TF-324T-6-BR-F-25		

GENERAL DATA		
Frame Size	324T	
Frame Enclosure	TEFC	
Mounting	Rigid	
Insulation Class	F	
Duty	Cont. / S1	
NEMA Design	A	
Frame Material	Cast Iron	
Ingress Protection	55	
Tropicalization	true	
Cable Entry	1-NPT 2"	
Feet Removable	true	
Double Drilled	-	
Paint Color	Graphite Gray	
Paint RAL	7024	
Weight lb	500.535	
MECHANICAL DATA		
DE Bearing	6312C3	
NDE Bearing	6312C3	
dB No-Load	-	
Rotor Wk ² , Lb-Ft ²	-	
Comp Ring (wavy washer)	DE	
TORQUE VALUES	Torque lb-ft	% FLT
Locked Rotor Torque	374.193	338.0
Pull-Up Torque	218.095	197.0
Breakdown Torque	464.974	420.0
Full Load Torque	110.708	100.0
SITE CONDITIONS		
Ambient Temp °C	40	
Altitude Above Sea Level m	1000	

*This report valid for above Date Code and newer models, please contact Techttop for more info.

Techtop Industries
 2815 Colonnades Court
 Peachtree Corners, GA 30071
 Tel: 678-436-5540
 E-Mail: info@techttopind.com



NEMA Premium


NEMA

MOTOR MODEL:	GR3-CI-TF-324T-6-BR-F-25
FACTORY TYPE:	TXC

Premium NEMA Cast Iron, TEFC

Non Sinusoidal (VFD) Output 25.0HP, 1180 RPM

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	374.193	338.0	Start Configuration
Pull-Up Torque	218.095	197.0	Starting Current (A)
Breakdown Torque	464.974	420.0	No-Load Current (A)
Full Load	110.708	100.0	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	14.61	-	-	-	-
25	6.25	16.05	5.35	1196.5	86.95	0.42
50	12.5	19.84	10.14	1193.1	91.71	0.64
75	18.75	24.87	15.04	1189.5	92.78	0.76
100	25.0	30.81	20.04	1185.7	92.81	0.82
125	31.25	34.69	23.1	1183.3	92.58	0.84

Techtop Industries
 2815 Colonnades Court
 Peachtree Corners, GA 30071
 Tel: 678-436-5540
 E-Mail: info@techttopind.com