

Techtop Industries Nameplate and Performance Data

NAMEPLATE DATA		
	60 Hz	50 Hz
Horsepower	1.0	-
Frame Size	143T	
Speed, RPM	1740	1420
Voltage	230/460	190/380
# Phase	3	
Full Load Amps	3.12/1.56	-
Power Factor	0.7	-
Nominal Efficiency	85.5	-
3/4 Load Efficiency	-	-
Service Factor	1.25	1.0
Duty	Cont. / S1	
FL Temp Rise °C	25.0	31.0
Enclosure	ODP	
Ambient Temp °C	-	
KVA Code	N	K
FL Amps. @ 208 V	3.15	-
Insulation Class	F	
NEMA Design	-	
Weight	-	
DE Bearing	6205ZZ	
NDE Bearing	6203ZZ	
dB No-Load	-	
Rotor Wk ² , Lb-Ft ²	-	
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	9	
Connection	YY/Y	
Coil Resistance	4.95	

Motor Model:	GR3-RS-OP-143T-4-B-D-1
---------------------	-------------------------------

Performance Load Values:

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	-	-	-	-	-
25	-	-	-	-	-	-
50	-	-	-	-	80.89	0.4857
75	-	-	-	-	84.77	0.6183
100	-	-	-	-	86.29	0.7088
125	-	-	-	-	-	-
150	-	-	-	-	-	-
SF	-	-	-	-	-	-

	Torque, Lb-Ft	% Full Load Torque	Speed, RPM	Current Amps.
Locked Rotor Torque	12.56	420.0	-	-
Pull Up Torque	9.87	330.0	-	-
Breakdown Torque	15.55	520.0	-	-
Full Load	2.99	100.0	-	-

Speed Torque Curve

Please contact Techtop for image.

Dimensional Drawing

Please contact Techtop for image.

Dimensions are for reference only. Allowance should be made for minor deviations in non standard specified properties.

3D Image Link: Not available for this motor