

## Techtop Industries Nameplate and Performance Data

NAMEPLATE DATA		
	60 Hz	50 Hz
<b>Horsepower</b>	2.0	-
<b>Frame Size</b>	145T	
<b>Speed, RPM</b>	3500	2860
<b>Voltage</b>	230/460	190/380
<b># Phase</b>	3	
<b>Full Load Amps</b>	5.28/2.64	-
<b>Power Factor</b>	0.83	-
<b>Nominal Efficiency</b>	85.5	-
<b>3/4 Load Efficiency</b>	-	-
<b>Service Factor</b>	1.25	1.0
<b>Duty</b>	Cont. / S1	
<b>FL Temp Rise °C</b>	25.0	39.0
<b>Enclosure</b>	ODP	
<b>Ambient Temp °C</b>	-	
<b>KVA Code</b>	K	G
<b>FL Amps. @ 208 V</b>	5.58	-
<b>Insulation Class</b>	F	
<b>NEMA Design</b>	-	
<b>Weight</b>	-	
<b>DE Bearing</b>	6205ZZ	
<b>NDE Bearing</b>	6203ZZ	
<b>dB No-Load</b>	-	
<b>Rotor Wk<sup>2</sup>, Lb-Ft<sup>2</sup></b>	-	
<b>Start Capacitor</b>	-	
<b>Start Capacitor V</b>	-	
<b>Run Capacitor</b>	-	
<b>Run Capacitor V</b>	-	
<b>Number of Leads</b>	9	
<b>Connection</b>	YY/Y	
<b>Coil Resistance</b>	3.95	

<b>Motor Model:</b>	<b>GR3-RS-OP-145T-2-B-D-2</b>
---------------------	-------------------------------

Performance Load Values:

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	-	-	-	-	-
25	-	-	-	-	-	-
50	-	-	-	-	85.1	0.6538
75	-	-	-	-	87.01	0.7746
100	-	-	-	-	87.06	0.8362
125	-	-	-	-	-	-
150	-	-	-	-	-	-
SF	-	-	-	-	-	-

	Torque, Lb-Ft	% Full Load Torque	Speed, RPM	Current Amps.
Locked Rotor Torque	8.49	280.0	-	-
Pull Up Torque	7.28	240.0	-	-
Breakdown Torque	11.37	375.0	-	-
Full Load	3.03	100.0	-	-

### Speed Torque Curve

Please contact Techtop for image.

### Dimensional Drawing

Please contact Techtop for image.

Dimensions are for reference only. Allowance should be made for minor deviations in non standard specified properties.

3D Image Link: Not available for this motor