



NEMA Premium

**NEMA**

<b>MOTOR MODEL:</b>	GR3-RS-OP-145T-2-B-D-3
<b>FACTORY TYPE:</b>	-

NEMA Rolled Steel, ODP

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	3.0	-
Speed, RPM	3500	2860
Voltage	230/460	190/380
# Phase	3	
Full Load Amps	7.56/3.78	-
Power Factor	0.86	-
Nominal Efficiency	86.5	-
3/4 Load Efficiency	-	-
Service Factor	1.25	1.0
KVA Code	K	G
FL Amps. @ 208 V	8.19	-
LRC @ 60Hz HV	-	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	9	
Connection	YY/Y	
Coil Resistance	2.51	
Date Code	-	
Load	Efficiency %	P.F.
50%	86.75	0.7083
75%	87.95	0.8174
100%	87.55	0.8658
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	37.0	56.0
3D Image Link		
<a href="#">GR3-RS-OP-145T-2-B-D-3</a>		

GENERAL DATA		
Frame Size	145T	
Frame Enclosure	ODP	
Mounting	Rigid	
Insulation Class	F	
Duty	Cont. / S1	
NEMA Design	-	
Frame Material	Rolled Steel	
Ingress Protection	23	
Tropicalization	true	
Cable Entry	1-NPT 3/4"	
Feet Removable	-	
Double Drilled	-	
Paint Color	Graphite Gray	
Paint RAL	7024	
Weight lb	-	
MECHANICAL DATA		
DE Bearing	6205ZZ	
NDE Bearing	6203ZZ	
dB No-Load	-	
Rotor Wk <sup>2</sup> , Lb-Ft <sup>2</sup>	-	
Comp Ring (wavy washer)	NDE	
TORQUE VALUES	Torque lb-ft	% FLT
Locked Rotor Torque	12.89	285.0
Pull-Up Torque	9.72	215.0
Breakdown Torque	16.73	370.0
Full Load Torque	4.52	100.0
SITE CONDITIONS		
Ambient Temp °C	-	
Altitude Above Sea Level m	-	

\*This report valid for above Date Code and newer models, please contact Techtop for more info.




NEMA Premium

**NEMA**

<b>MOTOR MODEL:</b>	GR3-RS-OP-145T-2-B-D-3
<b>FACTORY TYPE:</b>	-

NEMA Rolled Steel, ODP

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	12.89	285.0	Start Configuration
Pull-Up Torque	9.72	215.0	Starting Current (A)
Breakdown Torque	16.73	370.0	No-Load Current (A)
Full Load	4.52	100.0	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	-	-	-	-	-
25	-	-	-	-	-	-
50	-	-	-	-	86.75	0.7083
75	-	-	-	-	87.95	0.8174
100	-	-	-	-	87.55	0.8658
125	-	-	-	-	-	-

Techtop Industries  
 2815 Colonnades Court  
 Peachtree Corners, GA 30071  
 Tel: 678-436-5540  
 E-Mail: info@techttopind.com