



Definite Purpose

NEMA

| | |
|----------------------|--------------------------|
| MOTOR MODEL: | PC3-CI-TF-256T-4-BR-D-20 |
| FACTORY TYPE: | TFC |

NEMA Cast Iron, TEFC

| ELECTRICAL DATA | | |
|------------------------------|--------------|-------|
| | 60 Hz | 50 Hz |
| Horsepower | 20.0 | - |
| Speed, RPM | 1760 | - |
| Voltage | 230 | - |
| # Phase | 3 | |
| Full Load Amps | 45.76 | - |
| Power Factor | 0.83 | - |
| Nominal Efficiency | 93.0 | - |
| 3/4 Load Efficiency | - | - |
| Service Factor | 1.25 | - |
| KVA Code | K | - |
| FL Amps. @ 208 V | - | - |
| Locked Rotor Current | 211.318 | - |
| Start Capacitor | - | |
| Start Capacitor V | - | |
| Run Capacitor | - | |
| Run Capacitor V | - | |
| Number of Leads | 3 | |
| Connection | DD/D | |
| Coil Resistance | - | |
| Date Code | - | |
| | | |
| Load | Efficiency % | P.F. |
| 50% | 91.95 | 0.74 |
| 75% | 92.77 | 0.83 |
| 100% | 92.58 | 0.87 |
| | | |
| FULL LOAD TEMPERATURE RISE | | |
| FL Temp Rise °C | 51.0 | - |
| | | |
| 3D Image Link | | |
| Not available for this motor | | |

| GENERAL DATA | | |
|--|---------------|-------|
| Frame Size | 256T | |
| Frame Enclosure | TEFC | |
| Mounting | Rigid | |
| Insulation Class | F | |
| Duty | Cont. / S1 | |
| NEMA Design | A | |
| Frame Material | Cast Iron | |
| Ingress Protection | 55 | |
| Tropicalization | true | |
| Cable Entry | 1-NPT 1-1/4" | |
| Feet Removable | true | |
| Double Drilled | true | |
| Paint Color | Graphite Gray | |
| Paint RAL | 7024 | |
| Weight lb | 330.75 | |
| | | |
| MECHANICAL DATA | | |
| DE Bearing | 6309C3 | |
| NDE Bearing | 6309C3 | |
| dB No-Load | - | |
| Rotor Wk ² , Lb-Ft ² | - | |
| Comp Ring (wavey washer) | DE | |
| | | |
| TORQUE VALUES | Torque lb-ft | % FLT |
| Locked Rotor Torque | 166.907 | 280.0 |
| Pull-Up Torque | 122.796 | 206.0 |
| Breakdown Torque | 209.826 | 352.0 |
| Full Load Torque | 59.6098 | 100.0 |
| | | |
| SITE CONDITIONS | | |
| Ambient Temp °C | 40 | |
| Altitude Above Sea Level m | 1000 | |

*This report valid for above Date Code and newer models, please contact Techttop for more info.

Techtop Industries
 2815 Colonnades Court
 Peachtree Corners, GA 30071
 Tel: 678-436-5540
 E-Mail: info@techttopind.com



Definite Purpose


NEMA

| | |
|----------------------|--------------------------|
| MOTOR MODEL: | PC3-CI-TF-256T-4-BR-D-20 |
| FACTORY TYPE: | TFC |

NEMA Cast Iron, TEFC

Non Sinusoidal (VFD) Output 20.0HP, 1760 RPM

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

| Torque Values | Torque lb-ft | % FLT | Performance Values |
|---------------------|--------------|-------|----------------------|
| Locked Rotor Torque | 166.907 | 280.0 | Start Configuration |
| Pull-Up Torque | 122.796 | 206.0 | Starting Current (A) |
| Breakdown Torque | 209.826 | 352.0 | No-Load Current (A) |
| Full Load | 59.6098 | 100.0 | No-Load Power Factor |

| % Load | Horsepower | Current, Amps | Input power, Kilowatts | Speed, RPM | Efficiency | PF |
|--------|------------|---------------|------------------------|------------|------------|------|
| 0 | - | 8.72 | - | - | - | - |
| 25 | 5.0 | 10.25 | 4.28 | 1793.3 | 87.68 | 0.52 |
| 50 | 10.0 | 13.84 | 8.16 | 1786.6 | 91.95 | 0.74 |
| 75 | 15.0 | 18.28 | 12.13 | 1779.4 | 92.77 | 0.83 |
| 100 | 20.0 | 23.35 | 16.2 | 1771.7 | 92.58 | 0.87 |
| 125 | 25.0 | 28.86 | 20.39 | 1763.5 | 91.95 | 0.89 |

Techtop Industries
 2815 Colonnades Court
 Peachtree Corners, GA 30071
 Tel: 678-436-5540
 E-Mail: info@techttopind.com