



Single Phase

NEMA

MOTOR MODEL:	RD1-RS-TF-215T-4-B-B-10
FACTORY TYPE:	SLF

NEMA Rolled Steel, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	10.0	-
Speed, RPM	1740	-
Voltage	208-230	-
# Phase	1	-
Full Load Amps	46.3-41.8	-
Power Factor	0.94	-
Nominal Efficiency	83.0	-
3/4 Load Efficiency	-	-
Service Factor	1.15	-
KVA Code	H	-
FL Amps. @ 208 V	46.3	-
Locked Rotor Current	299.932	-
Start Capacitor	500 x2	-
Start Capacitor V	350	-
Run Capacitor	50 x2	-
Run Capacitor V	450	-
Number of Leads	5	-
Connection	-	-
Coil Resistance	-	-
Load	Efficiency %	P.F.
50%	-	-
75%	-	-
100%	-	-
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	93.0	-
3D Image Link		
RD1-RS-TF-215T-4-B-B-10		

GENERAL DATA			
Frame Size	215T		
Frame Enclosure	TEFC		
Mounting	Rigid		
Insulation Class	F		
Duty	Cont. / S1		
NEMA Design	L		
Frame Material	Rolled Steel		
Ingress Protection	54		
Tropicalization	-		
Cable Entry	1.1"		
Feet Removable	-		
Double Drilled	true		
Paint Color	Graphite Gray		
Paint RAL	7024		
Weight lb	207.0		
MECHANICAL DATA			
DE Bearing	6208-2RZ		
NDE Bearing	6206-2RZ		
dB No-Load	-		
Rotor Wk ² , Lb-Ft ²	-		
Comp Ring (wavey washer)	NDE		
TORQUE VALUES		Torque lb-ft	% FLT
Locked Rotor Torque	108.962	362.0	
Pull-Up Torque	58.9958	196.0	
Breakdown Torque	68.0258	226.0	
Full Load Torque	30.0999	100.0	
SITE CONDITIONS			
Ambient Temp °C	40		
Altitude Above Sea Level m	1000		



Single Phase


MOTOR MODEL:	RD1-RS-TF-215T-4-B-B-10
FACTORY TYPE:	SLF

NEMA

NEMA Rolled Steel, TEFC

Non Sinusoidal (VFD) Output 10.0HP, 1740 RPM

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	108.962	362.0	Start Configuration
Pull-Up Torque	58.9958	196.0	Starting Current (A)
Breakdown Torque	68.0258	226.0	No-Load Current (A)
Full Load	30.0999	100.0	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	-	-	-	-	-
25	-	-	-	-	-	-
50	-	-	-	-	-	-
75	-	-	-	-	-	-
100	-	-	-	-	-	-
125	-	-	-	-	-	-

Techtop Industries
 2815 Colonnades Court
 Peachtree Corners, GA 30071
 Tel: 678-436-5540
 E-Mail: info@techttopind.com