

## Techtop Industries Nameplate and Performance Data

NAMEPLATE DATA		
	60 Hz	50 Hz
<b>Horsepower</b>	2.0	-
<b>Frame Size</b>	56H	
<b>Speed, RPM</b>	1740	-
<b>Voltage</b>	115/208-230	-
<b># Phase</b>	1	
<b>Full Load Amps</b>	17.3/10.4-8.65	-
<b>Power Factor</b>	0.92	-
<b>Nominal Efficiency</b>	81.5	-
<b>3/4 Load Efficiency</b>	-	-
<b>Service Factor</b>	1.15	-
<b>Duty</b>	Cont. / S1	
<b>FL Temp Rise °C</b>	89.13	-
<b>Enclosure</b>	TEFC	
<b>Ambient Temp °C</b>	40	
<b>KVA Code</b>	H	-
<b>FL Amps. @ 208 V</b>	10.4	-
<b>Insulation Class</b>	F	
<b>NEMA Design</b>	L	
<b>Weight</b>	53.0	
<b>DE Bearing</b>	6204-2RZ	
<b>NDE Bearing</b>	6203-2RZ	
<b>dB No-Load</b>	-	
<b>Rotor Wk<sup>2</sup>, Lb-Ft<sup>2</sup></b>	-	
<b>Start Capacitor</b>	500	
<b>Start Capacitor V</b>	165	
<b>Run Capacitor</b>	80	
<b>Run Capacitor V</b>	250	
<b>Number of Leads</b>	7	
<b>Connection</b>	-	
<b>Coil Resistance</b>	-	

<b>Motor Model:</b>	<b>RD1-RS-TF-56H-4-B-C-2</b>
---------------------	------------------------------

Performance Load Values:

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	3.27	-	-	-	-
25	-	-	-	-	-	-
50	-	-	-	-	-	-
75	-	-	-	-	-	-
100	-	-	-	-	-	-
125	-	-	-	-	-	-
150	-	-	-	-	-	-
SF	-	-	-	-	-	-

	Torque, Lb-Ft	% Full Load Torque	Speed, RPM	Current Amps.
Locked Rotor Torque	-	-	-	-
Pull Up Torque	-	-	-	-
Breakdown Torque	-	-	-	-
Full Load	-	100.0	-	-

### Speed Torque Curve

Please contact Techtop for image.

### Dimensional Drawing

Please contact Techtop for image.

Dimensions are for reference only. Allowance should be made for minor deviations in non standard specified properties.

3D Image Link: Not available for this motor