



NEMA Premium

NEMA

MOTOR MODEL:	WX3-AL-TF-184T-2-B-D-5
FACTORY TYPE:	TXA

Premium NEMA Cast Aluminum, TEFC

ELECTRICAL DATA		
	60 Hz	50 Hz
Horsepower	5.0	5.0
Speed, RPM	3510	2900
Voltage	230/460	190/380
# Phase	3	
Full Load Amps	11.5/5.77	13.5/6.75
Power Factor	0.91	-
Nominal Efficiency	88.5	87.1
3/4 Load Efficiency	-	-
Service Factor	1.25	1.0
KVA Code	L	J
FL Amps. @ 208 V	12.7	-
Locked Rotor Current	61.2375	-
Start Capacitor	-	
Start Capacitor V	-	
Run Capacitor	-	
Run Capacitor V	-	
Number of Leads	9	
Connection	YY/Y	
Coil Resistance	-	
Load	Efficiency %	P.F.
50%	-	-
75%	-	-
100%	-	-
FULL LOAD TEMPERATURE RISE		
FL Temp Rise °C	45.0	45.0
3D Image Link		
WX3-AL-TF-184T-2-B-D-5		

GENERAL DATA				
Frame Size	184T			
Frame Enclosure	TEFC			
Mounting	Rigid			
Insulation Class	F			
Duty	Cont. / S1			
NEMA Design	A			
Frame Material	Cast Aluminum			
Ingress Protection	56			
Tropicalization	true			
Cable Entry	1-NPT 3/4"			
Feet Removable	true			
Double Drilled	-			
Paint Color	-			
Paint RAL	-			
Weight lb	62.0			
MECHANICAL DATA				
DE Bearing	6306ZZ			
NDE Bearing	6206ZZ			
dB No-Load	-			
Rotor Wk ² , Lb-Ft ²	-			
Comp Ring (wavy washer)	NDE			
TORQUE VALUES			Torque lb-ft	% FLT
Locked Rotor Torque	22.859	309.0		
Pull-Up Torque	-	-		
Breakdown Torque	17.3847	235.0		
Full Load Torque	7.39775	100.0		
SITE CONDITIONS				
Ambient Temp °C	40			
Altitude Above Sea Level m	1000			



NEMA Premium

MOTOR MODEL:	WX3-AL-TF-184T-2-B-D-5
FACTORY TYPE:	TXA

NEMA

Premium NEMA Cast Aluminum, TEFC

Non Sinusoidal (VFD) Output 5.0HP, 3510 RPM

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

Torque Values	Torque lb-ft	% FLT	Performance Values
Locked Rotor Torque	22.859	309.0	Start Configuration
Pull-Up Torque	-	-	Starting Current (A)
Breakdown Torque	17.3847	235.0	No-Load Current (A)
Full Load	7.39775	100.0	No-Load Power Factor

% Load	Horsepower	Current, Amps	Input power, Kilowatts	Speed, RPM	Efficiency	PF
0	-	1.91	-	-	-	-
25	1.25	-	-	-	-	-
50	2.5	-	-	-	-	-
75	3.75	-	-	-	-	-
100	5.0	-	-	-	-	-
125	6.25	-	-	-	-	-