






NEMA Premium

**NEMA**

|                      |                        |
|----------------------|------------------------|
| <b>MOTOR MODEL:</b>  | WX3-AL-TF-184T-4-B-D-5 |
| <b>FACTORY TYPE:</b> | TXA                    |

Premium NEMA Cast Aluminum, TEFC

Torque Speed (T-n) Curve



Performance Load Values, High Voltage, 60Hz

| Torque Values       | Torque lb-ft | % FLT | Performance Values   |
|---------------------|--------------|-------|----------------------|
| Locked Rotor Torque | 37.8741      | 253.0 | Start Configuration  |
| Pull-Up Torque      | 33.6825      | 225.0 | Starting Current (A) |
| Breakdown Torque    | 54.1914      | 362.0 | No-Load Current (A)  |
| Full Load           | 14.97        | 100.0 | No-Load Power Factor |

| % Load | Horsepower | Current, Amps | Input power, Kilowatts | Speed, RPM | Efficiency | PF |
|--------|------------|---------------|------------------------|------------|------------|----|
| 0      | -          | -             | -                      | -          | -          | -  |
| 25     | 1.25       | -             | -                      | -          | -          | -  |
| 50     | 2.5        | -             | -                      | -          | -          | -  |
| 75     | 3.75       | -             | -                      | -          | -          | -  |
| 100    | 5.0        | -             | -                      | -          | -          | -  |
| 125    | 6.25       | -             | -                      | -          | -          | -  |

Techtop Industries  
 2815 Colonnades Court  
 Peachtree Corners, GA 30071  
 Tel: 678-436-5540  
 E-Mail: info@techttopind.com